华巽云科技投资控股（青岛）集团有限责任公司

潜水打捞系统

型号：HXY-QS-01 | 品牌：CETIG 华巽云



产品简介

潜水打捞系统 · HXY-QS-01

华巽云科技投资控股（青岛）集团有限责任公司
0532-84123835（工作日 08:00–17:30） | huaxunyun2021@163.com | 山东省青岛市黄岛区海军路 1000 号
www.cetig.cn

本说明书内容以产品实际交付版本为准；规格如有变更，恕不另行通知。

技术参数

参数

潜水打捞系统：	Small lift bags≥2, medium lift bags≥2, underwater salvage kits (cylinder, electric low-pressure compressor, hose, regulator, gauge)≥4,
小型打捞袋：	Made of high-strength PVC-coated fabric, single-bag lifting capacity≥2000kg, strength≥5000N/cm, with overpressure relief valve, automatic and manual deflation, dedicated cylinder mount, two lifting rings at top and bottom, securing chain at the bottom。
中型打捞袋：	Made of high-strength PVC-coated fabric, single-bag lifting capacity≥4000kg, strength≥5000N/cm, with overpressure relief valve, valve opening pressure 16-24Kap, automatic and manual deflation, dedicated cylinder mount, two lifting rings at top and bottom, securing chain at the bottom。
水下打捞组件	①Cylinder made of 6061 aluminium alloy, with explosion-proof valve, offset valve stem, angled internal gas flow, prevents outlet freezing。Cylinder volume≥12L,wall thickness≥11mm, working pressure≥20MPA, weight≤16kg, cylinder diameter≥170mm, cylinder height≥700mm。
②Electric compressor with brushless variable-frequency motor, tank volume≥56L, working pressure0.3-1.0MPAadjustable, air delivery≥650L/min, power≥4.2KW, dimensions≤950mm*390mm*640mm	
③PVC inflation hose, outer diameter≥13mm, inner diameter≥7mm, quick connector to lift bag at one end, cylinder connector at the other end。	
④Regulator output pressure9.2-9.8bar, externally adjustable, low-pressure ports≥2, medium-pressure ports≥4, flow rate≥5000L/min, balanced diaphragm designprevents outlet freezing, weight≤720g。	
⑤Polished stainless-steel gauge housing, high-visibility black markings on a luminescent dial, readable at night。Gauge range0-360BARrange。	