
Hot-Water Diving Umbilical / Diving Umbilical

Model: QSQD-01 | Brand: CETIG 华巽云



Overview

Hot-Water Diving Umbilical / Diving Umbilical · QSQD-01

CETIG Technology Investment Holding (Qingdao) Group Co., Ltd.
+86 532 8412 3835 (Mon–Sat 08:00–17:30 CST) | huaxunyun2021@163.com | No. 1000 Haijun Road, Huangdao District, Qingdao, Shandong, China
www.cetig.cn

Specifications apply to the delivered product version and may change without notice.

Technical Specifications

The Hot-Water Diving Umbilical / Diving Umbilical is part of CETIG's product range, developed for demanding water-rescue and maritime safety operations. Key technical data are listed below.

Product specifications

Hot-water hose, depth hose, air hose, communication and reinforcement cable	
Hot-water hose ID 12.5 mm / OD 21 mm; max 25 bar; burst 100 bar	
Depth hose ID 6.3 mm / OD 12.7 mm; max 21 bar; burst 84 bar	
Hose ID 9.5 mm / OD 16.8 mm; max working pressure 35 bar; burst pressure 140 bar	
2 × 20 AWG shielded cable; 500 kg tensile load; min bend radius > 280 mm (dynamic), > 190 mm (static)	
Surface end connects to a diving air panel and diving telephone	
Length (m)	120/182 (hot-water umbilical), 100/120/160/182 (diving umbilical)