华巽云科技投资控股（青岛）集团有限责任公司

自扶正救生艇

型号：HXY-ZF-01 | 品牌：CETIG 华巽云



产品简介

自扶正救生艇 · HXY-ZF-01

华巽云科技投资控股（青岛）集团有限责任公司
0532-84123835（工作日 08:00–17:30） | huaxunyun2021@163.com | 山东省青岛市黄岛区海军路 1000 号
www.cetig.cn

本说明书内容以产品实际交付版本为准；规格如有变更，恕不另行通知。

技术参数

参数

10–12 independent air chambers, each with its own inflation valve.	
Self-righting function:after a manual 90° capsize and release,self-righting whitewater rescue boatreturns automatically to upright,crew remain safe,all functions remain operational after self-righting。	
Capacity 10–12 persons; maximum speed 50–65 km/h.	
Propulsion: propeller-driven	
Self-rights and powers normally regardless of deployment orientation。	
产品尺寸:	L × W × H: 4.6 × 2.3 × 2.2 m
外壳材料:	PVC-coated
总重量:	155 kg (5 kg), excluding outboard motor
续航距离（米）:	≥80km
舷外机功率:	60HP
Maximum speed > 50–65 km/h	
搭载人员:	Capacity > 10–12 persons
> 9 independent hull chambers, > 2 independent floor chambers	
Self-righting function keeps the crew safe and all vessel functions operational.	
Designed to carry personnel and equipment in whitewater, heavy surf and low-head dams, inflatable, foldable structure for easy transport	
Triangular rescue boat design, wide beam, twin pressurised side tubes。multi-layer reinforced composite hull:rigid inner layer。	
Reinforced abrasion-resistant armour strips on the hull bottom。One-piece hull design, multi-layer reinforced seams, two self-righting columns can be deflated independently, to reduce overall height, twin pressurised tubes on both sideshullextra abrasion reinforcement on top	
Detachable hull bottom, hull bottomintegrated spray rails on both sidesdouble-layer overlapping drop-stitch air floor;Rubber-coated hull fabric: warp tensile strength 86.0 kN/m。weft tensile strength 61.5 kN/m 。 warp trapezoidal tear strength 418 N 。	
The stern recesses the outboard motor into the hull; the seat beam and transom are integrated and seawater-corrosion resistant.10 independent air chambers, each with its own inflation valve, Hull length≥4.6m; hull width≥2.3m; hull height2.2.m	
充气装置:	Standard foot pump; 220 V and 12 V inflation also available.
高处救援:	Two adults standing on the upturned boat cause no visible deformation or tipping of the top air column

Reflective markings around the hull,grab handles and straps around the hull

华巽云科技投资控股（青岛）集团有限责任公司
0532-84123835（工作日 08:00–17:30） | huaxunyun2021@163.com | 山东省青岛市黄岛区海军路 1000 号

本说明书内容以产品实际交付版本为准；规格如有变更，恕不另行通知。